

Article-No: 9131160

Profile luminaire




KATLA LED 1.5m PCO 1x37W 120° 4900lm 840 TW3x1,5 class I

Damp proof surface lamp with slim, flat, fully sealed housing made of translucent, opal polycarbonate (impact resistant), end caps made of PBT (shatter proof), short, age-resistant silicone seals, easy installation with two spacious rooms of power supply, high performance LED, wide-angle light distribution with ceiling illumination, easily exchangeable, built-in converter, variable mounting points through PRACHT-CLIP-SYSTEM (stainless steel), suitable for ceiling and horizontal wall mounting, accessories for pendant and mounting rail installation available for order.

GTIN 4018098234722

Statistical product number 94054231



DIMENSIONS AND WEIGHTS

Length	1465 mm
Width	59 mm
Height	62 mm
Net weight	1,50 kg

OUTPUT

Luminous flux	4900 lm
Systempower	37 W
Efficacy	132 lm/W
Energy efficiency class of the light source	D

ASSEMBLY AND MAINTENANCE

Optional mounting type	Pendulum mounting, mounting rail, horizontal Wall
Standard mounting	Ceiling

MATERIAL

Cover material	PCO - Polycarbonate OPAL
Housing material	PC-OPAL
Housing colour	opalized

LIGHT SOURCE

Luminaire type	LED
Number of light sources LED rows lamps	1
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	144
Standard Deviation of Colour Matching (SDCM)	5
Control gear exchangeable	yes, by qualified person
Light source exchangeable	yes, by qualified person

LIGHTING ENGINEERING

Light distributor	Diffuser lens/optic/panel
Light distribution angle	120 °
Light distribution	wide beam
Glare limitation UGR 4H 8H C0 C90	25 / 26

CAPACITY

outdoor area	Protected outdoor area*
Rebuildable	false
IK-Impact resistance	IK07
Protection class (IP)	IP66
Use in animal husbandry	not suitable
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L80/B50 25°C	62256
L70/B50 25°C	97763
Life expectancy B10 at 25° in hours (h)	
L80/B10 25°C	62256
L70/B10 25°C	87442
Life expectancy B50 at 35° in hours (h)	
L80/B50 35°C	56436
L70/B50 35°C	88348
max. lowest temperature	-20 °C
max. highest temperature	35 °C

TECHNICAL DATA

Dimming type	No dim function
Filament test	850 °C
Protection class	class I
Circuit Breaker B10A	22 Luminaires
Circuit Breaker B16A	35 Luminaires
Circuit Breaker C10A	35 Luminaires
Circuit Breaker C16A	57 Luminaires
Voltage spike protection U (L-PE)	2,0 kV
Voltage spike protection U (L-N)	1,0 kV
Through-wiring mm ²	3x1,5
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	According to area of application
Emergency light suitability of the luminaire	Yes, with article number 9131160NZ
Rated voltage	220–240V 0/50 Hz

PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	1,50 m
Width	0,07 m
Height	0,07 m
Weight	1,70 kg
VPE 2	
Unit	Pallet
Content quantity	154 Piece
Length	1,47 m
Width	0,80 m
Height	1,10 m
Weight	281,80 kg

FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

Accessories (optional)

Article-No:	Designation
0604222	Rope-/chain suspension bracket LUNA N made of stainless steel

* Protected outdoor area:
a canopy protects the luminaire of direct solar radiation.
It is to be ensured that for mounting beneath the edge,
the luminaire does not withstand heavy rainfall. Typically a
height difference of 0,5 times the roof overhang compared
to the luminaire should not be exceeded.

The right of error and later technical developments is reserved. 15.08.2024

Values may be extrapolated differently from TM21.

