

Article-No: 86040721

High Bay




**QUADRONIUS DALI 77cm ESG  
2x137W 115° 40000lm 840  
TWwithout class I**

LED High Bay with single pane safety glass lamp cover, housing made of die cast aluminium, white coating, converter mounted on the housing, electrical connection through free cable end, short, ageing-resistant silicone seals, two-point mounting with suspension (2000 mm), easy to assemble, tool-free, rapid adjustment, pendant mounting, mounting brackets for optional wall or ceiling mounting available for order.

GTIN 4018098322795

Statistical product number 94054239



**DIMENSIONS AND WEIGHTS**

Length	768 mm
Width	324 mm
Height	157 mm
Net weight	14,00 kg

**OUTPUT**

Luminous flux	40000 lm
Systempower	274 W
Efficacy	146 lm/W
Energy efficiency class of the light source	E

## ASSEMBLY AND MAINTENANCE

Optional mounting type	Ceiling, horizontal Wall, vertical wall
Standard mounting	Pendulum mounting

## LIGHT SOURCE

Luminaire type	LED
Number of light sources   LED rows   lamps	2
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	512
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	yes, by qualified person
Light source exchangeable	yes, by qualified person

## LIGHTING ENGINEERING

Light distributor	none
Light distribution angle	115 °
Light distribution	wide beam
Glare limitation UGR 4H 8H C0 C90	31 / 30

## CAPACITY

outdoor area	Protected outdoor area*
Rebuildable	false
IK-Impact resistance	IK08
Protection class (IP)	IP65
Use in animal husbandry	with limitation
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L80/B50 25°C	70000
L70/B50 25°C	100000
Life expectancy B10 at 25° in hours (h)	
L80/B10 25°C	70000
L70/B10 25°C	100000
Life expectancy B50 at 45° in hours (h)	
L70/B50 45°C	65000
max. lowest temperature	-40 °C
max. highest temperature	45 °C

## MATERIAL

Cover material	single-pane safety glass
Housing material	Aluminium
Housing colour	White RAL 9010

## TECHNICAL DATA

Dimming type	Dimming DALI Dimming DALI-2
Filament test	960 °C
Protection class	class I
Circuit Breaker B10A	4 Luminaires
Circuit Breaker B16A	7 Luminaires
Circuit Breaker C10A	7 Luminaires
Circuit Breaker C16A	11 Luminaires
Voltage spike protection U (L-PE)	10,0 kV
Voltage spike protection U (L-N)	6,0 kV
Through-wiring mm²	without
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	false
Emergency light suitability of the luminaire	No
Rated voltage	220–240V 0/50/60 Hz

## PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	0,81 m
Width	0,35 m
Height	0,23 m
Weight	16,50 kg
VPE 2	
Unit	Pallet
Content quantity	15 Piece
Length	1,20 m
Width	0,80 m
Height	1,30 m
Weight	267,50 kg

## FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

## Accessories (optional)

---

Article-No:	Designation
06011071	Wall and ceiling mounting bracket Quadronius, coated RAL 9010
06011081	Ceiling mounting bracket Quadronius two angle, coated RAL 9010
06012171	Wall and ceiling mounting bracket Quadronius POOL, coated RAL 9010, V4A
06012181	Ceiling mounting bracket Quadronius POOL two angle, coated RAL 9010, V4A

\* Protected outdoor area:  
a canopy protects the luminaire of direct solar radiation. It is to be ensured that for mounting beneath the edge, the luminaire does not withstand heavy rainfall. Typically a height difference of 0,5 times the roof overhang compared to the luminaire should not be exceeded.

*The right of error and later technical developments is reserved. 15.08.2024*

Values may be extrapolated differently from TM21.

