

Article-No: 86130101
High Bay




QUADRONIUS FOOD 29cm PC 1x97W 090° 15000lm 840 TWwithout class I

LED High Bay with polycarbonate cover (translucent, shatterproof), hygienic, low maintenance and dustproof because of a shatterproof PC-pane, housing made of die cast aluminium, white coating, converter integrated in the housing, electrical connection through fast plug-in, short, age-resistant silicone seals, two-point mounting with suspension (2000 mm), easy to assemble, tool-free, rapid adjustment, pendant mounting, mounting brackets for optional wall or ceiling mounting available for order.

GTIN 4018098327196
Statistical product number 94054239

86130101



DIMENSIONS AND WEIGHTS

Length	288 mm
Width	288 mm
Height	170 mm
Net weight	6,00 kg

ASSEMBLY AND MAINTENANCE

Optional mounting type	Ceiling, horizontal Wall, vertical wall
Standard mounting	Pendulum mounting

LIGHT SOURCE

Luminaire type	LED
Number of light sources LED rows lamps	1
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	256
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	yes, by qualified person
Light source exchangeable	yes, by qualified person

LIGHTING ENGINEERING

Light distributor	Refractor lens
Light distribution angle	90 °
Light distribution	wide beam
Glare limitation UGR 4H 8H C0 C90	26 / 26

OUTPUT

Luminous flux	15000 lm
Systempower	97 W
Efficacy	155 lm/W
Energy efficiency class of the light source	E

MATERIAL

Cover material	PC - Polycarbonate
Housing material	Aluminium
Housing colour	White RAL 9010

CAPACITY

outdoor area	Protected outdoor area*
Rebuildable	false
IK-Impact resistance	IK10
Protection class (IP)	IP66
Use in animal husbandry	not suitable
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L80/B50 25°C	80000
L70/B50 25°C	100000
Life expectancy B10 at 25° in hours (h)	
L80/B10 25°C	80000
L70/B10 25°C	100000
Life expectancy B50 at 45° in hours (h)	
L80/B50 45°C	55000
L70/B50 45°C	86000
max. lowest temperature	-30 °C
max. highest temperature	45 °C

TECHNICAL DATA

Dimming type	No dim function
Filament test	960 °C
Protection class	class I
Circuit Breaker B10A	7 Luminaires
Circuit Breaker B16A	11 Luminaires
Circuit Breaker C10A	13 Luminaires
Circuit Breaker C16A	21 Luminaires
Voltage spike protection U (L-PE)	10,0 kV
Voltage spike protection U (L-N)	6,0 kV
Through-wiring mm ²	without
D-marking	true
Voltage type acc. ETIM	AC
IFS suitable	true
Emergency light suitability of the luminaire	No
Rated voltage	220-240V 50/60 Hz

PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	0,35 m
Width	0,35 m
Height	0,26 m
Weight	8,50 kg
VPE 2	
Unit	Pallet
Content quantity	30 Piece
Length	1,20 m
Width	0,80 m
Height	1,19 m
Weight	275,00 kg

FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

Accessories (optional)

Article-No:	Designation
06011071	Wall and ceiling mounting bracket Quadronius, coated RAL 9010
06011081	Ceiling mounting bracket Quadronius two angle, coated RAL 9010
06012171	Wall and ceiling mounting bracket Quadronius POOL, coated RAL 9010, V4A
06012181	Ceiling mounting bracket Quadronius POOL two angle, coated RAL 9010, V4A

* Protected outdoor area:
a canopy protects the luminaire of direct solar radiation. It is to be ensured that for mounting beneath the edge, the luminaire does not withstand heavy rainfall. Typically a height difference of 0,5 times the roof overhang compared to the luminaire should not be exceeded.

The right of error and later technical developments is reserved. 15.08.2024

Values may be extrapolated differently from TM21.

