


Article-No: 86380621

High Bay




QUADRONIUS INDUSTRY DALI 91cm ESG 2x134W 065° 29900lm 840 TW without class I

LED High Bay with single pane safety glass lamp cover, especially designed for tough industrial surroundings. Suitable for ambient temperatures of -40°C and up to +50°C, Die-cast aluminum housing, white coating, converter integrated in housing, electrical connection through fast plug-in, short ageing-resistant silicone seals, two-point mounting with rope pendant (2.000 mm) with easy to install, tool-less quick adjustment, optional wall/ceiling mounting bracket.

GTIN 4018098267638

Statistical product number 94054239

86380621



DIMENSIONS AND WEIGHTS

Length	912 mm
Width	288 mm
Height	135 mm
Net weight	15,50 kg

OUTPUT

Luminous flux	29900 lm
Systempower	268 W
Efficacy	112 lm/W
Energy efficiency class of the light source	D

ASSEMBLY AND MAINTENANCE

Optional mounting type	Ceiling, horizontal Wall, vertical wall
Standard mounting	Pendulum mounting

LIGHT SOURCE

Luminaire type	LED
Number of light sources LED rows lamps	2
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	128
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	yes, by qualified person
Light source exchangeable	yes, by qualified person

LIGHTING ENGINEERING

Light distributor	Refractor lens
Light distribution angle	65 °
Light distribution	medium beam
Glare limitation UGR 4H 8H C0 C90	22 / 22

MATERIAL

Cover material	single-pane safety glass
Housing material	Aluminium
Housing colour	White RAL 9010

CAPACITY

outdoor area	Protected outdoor area*
Rebuildable	false
IK-Impact resistance	IK08
Protection class (IP)	IP65
Use in animal husbandry	not suitable
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L90/B50 25°C	100000
L80/B50 25°C	100000
L70/B50 25°C	100000
Life expectancy B10 at 25° in hours (h)	
L90/B10 25°C	100000
L80/B10 25°C	100000
L70/B10 25°C	100000
Life expectancy B50 at 50° in hours (h)	
L90/B50 50°C	100000
L80/B50 50°C	100000
L70/B50 50°C	100000
max. lowest temperature	-40 °C
max. highest temperature	50 °C

TECHNICAL DATA

Dimming type	Dimming DALI
Filament test	960 °C
Protection class	class I
Circuit Breaker B10A	1 Luminaires
Circuit Breaker B16A	2 Luminaires
Circuit Breaker C10A	2 Luminaires
Circuit Breaker C16A	3 Luminaires
Voltage spike protection U (L-PE)	6,0 kV
Voltage spike protection U (L-N)	6,0 kV
Through-wiring mm ²	without
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	false
Emergency light suitability of the luminaire	No
Rated voltage	220-240V 0/50/60 Hz

PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	0,99 m
Width	0,35 m
Height	0,23 m
Weight	18,60 kg
VPE 2	
Unit	Pallet
Content quantity	10 Piece
Length	1,20 m
Width	0,80 m
Height	1,30 m
Weight	206,00 kg

FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

Accessories (optional)

Article-No:	Designation
06011071	Wall and ceiling mounting bracket Quadronius, coated RAL 9010
06011081	Ceiling mounting bracket Quadronius two angle, coated RAL 9010
06012171	Wall and ceiling mounting bracket Quadronius POOL, coated RAL 9010, V4A
06012181	Ceiling mounting bracket Quadronius POOL two angle, coated RAL 9010, V4A

* Protected outdoor area:
 a canopy protects the luminaire of direct solar radiation. It is to be ensured that for mounting beneath the edge, the luminaire does not withstand heavy rainfall. Typically a height difference of 0,5 times the roof overhang compared to the luminaire should not be exceeded.

The right of error and later technical developments is reserved. 15.08.2024

Values may be extrapolated differently from TM21.

