

Article-No: 74833749


Recessed luminaires



## TAUNUS SKII DALI 185 1.2m PC 1x40W A060° 5300lm 940 TW5x2,5+2x1,5 class II 4kVESB

LED luminaire for flush-mounted installation. With cover made of either polycarbonate (PC) or PRACHTOPAL (PO). Luminaire housing made of polyester, white.. With MID-power LEDs, converter integrated in luminaire, with short ageing-resistant silicone seals, suitable for ceiling mounting, recess frame for built-in optionally available. IK08.

GTIN 4018098349969  
Statistical product number 94054231



### DIMENSIONS AND WEIGHTS

Length	1246 mm
Width	192 mm
Height	137 mm
Net weight	4,20 kg

### ASSEMBLY AND MAINTENANCE

Optional mounting type	Recessed
Standard mounting	Ceiling

### OUTPUT

Luminous flux	5300 lm
Systempower	40 W
Efficacy	132 lm/W
Energy efficiency class of the light source	D

### MATERIAL

Cover material	PC - Polycarbonate
Housing material	GRP polyester
Housing colour	white

## LIGHT SOURCE

Luminaire type	LED
Number of light sources   LED rows   lamps	1
Colour temperature	4000 K
Colour rendering index	>90
Number of LEDs	192
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	yes, by qualified person
Light source exchangeable	not exchangeable

## LIGHTING ENGINEERING

Light distributor	Diffuser lens/optic/panel
Light distribution angle	60 °
Light distribution	asymmetric
Glare limitation UGR 4H 8H C0 C90	20 / 14

## CAPACITY

outdoor area	Protected outdoor area*
Rebuildable	false
IK-Impact resistance	IK08
Protection class (IP)	IP65
Use in animal husbandry	not suitable
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L90/B50 25°C	56231
L80/B50 25°C	>100000
L70/B50 25°C	>100000
Life expectancy B10 at 25° in hours (h)	
L80/B10 25°C	>100000
L70/B10 25°C	>100000
Life expectancy B50 at 35° in hours (h)	
L90/B50 35°C	52531
L80/B50 35°C	>100000
L70/B50 35°C	>100000
max. lowest temperature	-25 °C
max. highest temperature	35 °C

## TECHNICAL DATA

Dimming type	Dimming DALI Dimming DALI-2
Filament test	650 °C
Protection class	class II
Circuit Breaker B10A	26 Luminaires
Circuit Breaker B16A	41 Luminaires
Circuit Breaker C10A	26 Luminaires
Circuit Breaker C16A	41 Luminaires
Voltage spike protection U (L-N)	4,0 kV
Through-wiring mm²	5x2,5+2x1,5
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	false
Emergency light suitability of the luminaire	Yes, with article number 74833749NZ
Rated voltage	220-240V 0/50/60 Hz

## PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	1,34 m
Width	0,20 m
Height	0,17 m
Weight	4,50 kg
VPE 2	
Unit	Pallet
Content quantity	28 Piece
Length	1,65 m
Width	0,80 m
Height	1,30 m
Weight	146,00 kg

## FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

\* Protected outdoor area:  
a canopy protects the luminaire of direct solar radiation. It is to be ensured that for mounting beneath the edge, the luminaire does not withstand heavy rainfall. Typically a height difference of 0,5 times the roof overhang compared to the luminaire should not be exceeded.

*The right of error and later technical developments is reserved. 15.08.2024*

Values may be extrapolated differently from TM21.

