

Article-No: 7a041429

Round tube luminaire




TUBIS LED INDUSTRY DALI 1.3m PC 1x29W 135° 4600lm 840 TWwithout class I

Tubular lamp highest industry demands made of impact resistant PRACHTOPAL® or polycarbonate (clear). Pressurised-water resistant tube, substantially acid and alkali resistant, diameter 90mm. Integrated robust industry LED driver. Homogeneous light output due to smart MID-Power LED layout. Several light output angles available thanks to linear lens system. Optimized thermal management due to X-Wing cooling profile. Through-wiring up to maximum 5x2.5mm² available. Short ageing-resistant silicone seals. Ingress protection IP66/IP68(2m)/IPX9K. Variable mounting points using stainless steel PRACHT tube clips, suitable for ceiling-, horizontal and vertical wall mounting, accessories for pendant and mounting rail installation available for order.

GTIN 4018098286707

Statistical product number 94054231



DIMENSIONS AND WEIGHTS

Length	1270 mm
Width	90 mm
Height	105 mm
Net weight	4,20 kg

OUTPUT

Luminous flux	4600 lm
Systempower	29 W
Efficacy	159 lm/W
Energy efficiency class of the light source	C

ASSEMBLY AND MAINTENANCE

Optional mounting type	Pendulum mounting, horizontal Wall, vertical wall
Standard mounting	Ceiling

MATERIAL

Cover material	PC - Polycarbonate
Housing material	PC-Polycarbonate
Housing colour	clear

LIGHT SOURCE

Luminaire type	LED
Number of light sources LED rows lamps	1
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	144
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	yes, by qualified person
Light source exchangeable	yes, by manufacturer

LIGHTING ENGINEERING

Light distributor	Refractor lens
Light distribution angle	135 °
Light distribution	wide beam
Glare limitation UGR 4H 8H C0 C90	21 / 25

CAPACITY

outdoor area	Unprotected outdoor area in the direct vicinity of the building with cable entry from below or from the side
Rebuildable	false
IK-Impact resistance	IK08
Protection class (IP)	IP66, IP68 (2m), IPX9, IPX9K
Use in animal husbandry	not suitable
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L90/B50 25°C	73730
L80/B50 25°C	>100000
L70/B50 25°C	>100000
Life expectancy B10 at 25° in hours (h)	
L90/B10 25°C	59851
L80/B10 25°C	>100000
L70/B10 25°C	>100000
Life expectancy B50 at 50° in hours (h)	
L90/B50 50°C	62816
L80/B50 50°C	>100000
L70/B50 50°C	>100000
max. lowest temperature	-30 °C
max. highest temperature	50 °C

TECHNICAL DATA

Dimming type	Dimming DALI Dimming DALI-2
Filament test	650 °C
Protection class	class I
Circuit Breaker B10A	21 Luminaires
Circuit Breaker B16A	36 Luminaires
Voltage spike protection U (L-PE)	4,0 kV
Voltage spike protection U (L-N)	4,0 kV
Through-wiring mm ²	without
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	true
Emergency light suitability of the luminaire	Yes, with article number 7a041429NZ
Rated voltage	220-240V 0/50/60 Hz

PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	1,55 m
Width	0,10 m
Height	0,09 m
Weight	4,40 kg
VPE 2	
Unit	Pallet
Content quantity	60 Piece
Length	1,70 m
Width	0,80 m
Height	1,20 m
Weight	284,00 kg

FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

Accessories (optional)

Article-No:	Designation
0706040	Pendulum mounting set Tubis, V2A clamp for pendulum mounting (2 pieces)

Spare parts

Article-No: Designation

0694038 Mounting clip TUBIS V2A complete

The right of error and later technical developments is reserved. 15.08.2024

Values may be extrapolated differently from TM21.

