


Article-No: 7c831859
 Round tube luminaire



**TUBIS LED RESISTANT DALI
 1.3m PO 1x58W 125° 8400lm
 840 TW5x2,5+2x1,5 class II**

LED tubular luminaire for extreme areas of application, optimized for livestock breeding as well as unprotected exterior and gas polluted areas. Welded tubular housing made of PRACHTOPAL (PMMA, impact resistant) with welded stainless steel end caps. Either integrated electrical supply cable (2m length) with open cable ends or circular connector (RST). Inclusive high quality electronic components, MID-Power LED technology for a homogeneous light output. Different types for standard on/off or DALI control are available. Luminaire in mounting rings rotatable, substantially acid and alkali resistant. Extreme short ageing-resistant silicone seals, variable mounting distances by PRACHT-stainless steel-rings, suitable for ceiling, horizontal and vertical wall mounting, accessories for pendant and mounting rail installation available for order, also approved for unprotected outdoor application.



GTIN 4018098373124
 Statistical product number 94054231

DIMENSIONS AND WEIGHTS

Length	1285 mm
Width	90 mm
Height	105 mm
Net weight	4,00 kg

OUTPUT

Luminous flux	8400 lm
Systempower	58 W
Efficacy	145 lm/W
Energy efficiency class of the light source	C

ASSEMBLY AND MAINTENANCE

Optional mounting type	Pendulum mounting, horizontal Wall, vertical wall
Standard mounting	Ceiling

LIGHT SOURCE

Luminaire type	LED
Number of light sources LED rows lamps	1
Colour temperature	4000 K
Colour rendering index	>80
Number of LEDs	144
Standard Deviation of Colour Matching (SDCM)	3
Control gear exchangeable	not exchangeable
Light source exchangeable	not exchangeable

LIGHTING ENGINEERING

Light distributor	Diffuser lens/optic/panel
Light distribution angle	125 °
Light distribution	wide beam
Glare limitation UGR 4H 8H C0 C90	24 / 27

CAPACITY

outdoor area	Unprotected outdoor area in the direct vicinity of the building with cable entry from below or from the side
Rebuildable	false
IK-Impact resistance	IK08
Protection class (IP)	IP66, IP68 (2m), IPX9, IPX9K
Use in animal husbandry	without limitation
Vandalism protection	false
Warranty	5 Years
Life expectancy B50 at 25° in hours (h)	
L80/B50 25°C	>100000
L70/B50 25°C	>100000
Life expectancy B10 at 25° in hours (h)	
L80/B10 25°C	>100000
L70/B10 25°C	>100000
Life expectancy B50 at 40° in hours (h)	
L80/B50 40°C	91731
L70/B50 40°C	>100000
max. lowest temperature	-30 °C
max. highest temperature	40 °C

MATERIAL

Cover material	PO - PRACHTOPAL
Housing material	PRACHTOPAL
Housing colour	opalized

TECHNICAL DATA

Dimming type	Dimming DALI Dimming DALI-2
Filament test	650 °C
Protection class	class II
Circuit Breaker B10A	15 Luminaires
Circuit Breaker B16A	24 Luminaires
Circuit Breaker C10A	24 Luminaires
Circuit Breaker C16A	40 Luminaires
Voltage spike protection U (L-PE)	4,0 kV
Voltage spike protection U (L-N)	2,0 kV
Through-wiring mm ²	5x2,5+2x1,5
D-marking	true
Voltage type acc. ETIM	AC/DC
IFS suitable	true
Emergency light suitability of the luminaire	No
Rated voltage	220–240V 0/50/60 Hz

PACKAGING

VPE 1	
Unit	Carton
Content quantity	1 Piece
Length	1,55 m
Width	0,10 m
Height	0,09 m
Weight	4,20 kg
VPE 2	
Unit	Pallet
Content quantity	60 Piece
Length	1,70 m
Width	0,80 m
Height	1,20 m
Weight	272,00 kg

FURTHER PRODUCT INFORMATION

REACH-Info	false
REACH-Listdate	2024-01-23
Market labelling	CE
Product labelling	RoHS, WEEE

The right of error and later technical developments is reserved. 15.08.2024

Values may be extrapolated differently from TM21.

